




www.frontierpower.com

PowerLine™ Model KS750-T3 7.5 kWe Generator



General Information* - Single Phase Rating

- The generator set rating is 6.5 kilowatts prime power output and 7.5 kilowatts intermittent or standby power output. These ratings are based upon standard rating conditions. It may be necessary to derate the set's output for altitudes above 1000' (300 meters) or for ambient temperatures above 104 F (40 C). Please contact the manufacturer for details on ratings criteria for the engine and generator or for derate information.
- The engine and brushless four pole AC generator are directly coupled and mounted on a rugged steel base frame. All components are suitable for prime or intermittent usage.
- The entire set is thoroughly load tested prior to shipment.

Standard Engine

- Kubota diesel model D1005BG-3. In-line, three-cylinder engine with full flow, replaceable lube oil, fuel and air filters. Mechanical speed governing provides better than 5% speed regulation, no load to full load. EPA tier 4. (Meets other emissions standards, consult factory.)
- Liquid cooled with industrial grade radiator and belt driven blower fan.
- SAE housing and flywheel, directly connected, single bearing generator. (CCW rotation)

Standard Generator

- Newage Stamford brushless, four pole (1800 rpm) generator.
- Solid state, +/- 1% automatic voltage regulation.
- CSA approved construction.

Standard Controls and Accessories

- Key start panel with oil pressure, coolant temperature, hour meter and glow plug indicator.
- Manual safety shutdown over-ride, fuse protection.
- Safety shutdowns, energized-to-run, for low oil pressure/high coolant temperature.
- Four anti-vibration mounts between generator set and base frame.
- Electric fuel transfer and priming pump (12 VDC).
- Battery rack and cables (no battery) for 12 VDC starting system.

Engine Technical Information

Manufacturer	Kubota
Model	D1005BG-3
Cylinders	Three
Bore X Stroke	76mm X 73.6mm (2.99" X 2.90")
Displacement	1001 cc (61.08 cu.in.)
Output, inter.	9.8 kWm (13.1 HP)
Output, cont.	8.7 kWm (11.7 HP)
Comp. ratio	24:1
Engine weight	110 kg (242 lbs.) dry
Fuel System	
Fuel type	#2 Diesel
Injection pump	Bosch PFR
Nozzle type	Throttle type
Transfer pump	Electric, 12VDC
Fuel lift	1 meter (3.3 ft.)
Suction fitting	5/16" push-on
Return fitting	3/16" push-on
Specific Fuel Consumption (Inter. Rating)	0.247 kg/kW/hr (ISO 3046) 0.406 lb/HP/hr (SAE J1349)
(Actual fuel consumption varies with site conditions and fuel energy content.)	

Lube Oil System

Grade	API Classification CF or other approved – see owner's manual
Capacity	5.1 liters (1.3 US gal.)
Forced feed by	trochoidal pump
Filter	Full flow, spin-on

Air Intake System

Filter	Replaceable element
- Combustion air	0.84 m ³ /min. (29.7 cfm)
Total system restriction	500mm (20") H ₂ O

DC Electrical System

Starter	12V, 1.0 kW
Alternator	12V, 30 Amp.
Glow plugs	In combustion chambers
Battery required	12V 65 AH equivalent, min.
Run solenoid	12V, ETR

Cooling System

Radiator	Finned tube type
Material	Copper core, soldered tanks
Pressure	88 kPa (12.9 psi) max
Fan type	Blower, Nylon
Water pump	Gear case mounted
Type	Centrifugal, belt drive
Thermostat	Wax pellet type
Stat. cracking temp.	71C (160F)

Cooling System, cont'd.

Fully open stat. temp.	85C (185F)
Recommended coolant	50/50*
Use low silicate ethylene glycol and high quality water. Consult manufacturer for details.	
Air-to-boil @ 7.0 kW _e	50C (122F)
Cooling air required	31.9 m ³ /min (1126 cfm)

Exhaust System

Muffler type	Industrial grade
Mounting	Vertical with rain cap
Restriction	38mm (1.5") Hg max.

Noise Level @ 1 m (3.3')

Levels are with industrial grade muffler and open (no enclosure) configuration.

Full load, inter.	81.6 dB (A)
Full load, prime	81.4 dB (A)
No load	80.2 dB (A)

Generator Technical Information

Manufacturer	Newage/Stamford
Model	PI044D (Standard)
Construction	Four pole, brushless Open drip-proof (IP23) Single bearing
Excitation (std.)	Full wave bridge rectifier
Excitation (opt.)	"Excitation Boost System" - Provides up to 300% current for motor starting
Cooling air flow	8.1 m ³ /min (286 cfm)
Leads	4 or 12, application dependent
60 Hz voltages and ratings - 6.5/7.4 kW, 6.5/7.0 kVA 120/240 - 1φ - 7.0/7.5 kW, 8.75/9.375 kVA 120/208 - 3φ - 7.0/7.5 kW, 8.75/9.375 kVA 277/480 3φ 50 Hz ratings and other voltages are available. Contact manufacturer for motor starting details.	
Power Factor	Single phase ratings @ 1.0 PF Three phase ratings @ 0.8 PF
Voltage reg.	AS480 solid state +/- 1% NL -> FL
Temp. rise	105C rise Prime (40C ambient) 125C rise Intermittent (40C)
Tel. interference	THF < 2%
Winding pitch	Two thirds
Control system	Self excited
Ancillary Equipment	
Mounting	Steel base with mounting holes
Isolators	Four composite mounts