

GENERAL ENGINE DATA

Type	-----	4-Cycle, Water Cooled	
Aspiration	-----	Turbo-Charged, Inter Cooler (Fresh water to Cooler)	
Cylinder Arrangement	-----	60°V	
No. of Cylinders	-----	12	
Bore mm(in.)	-----	170	(6.69)
Stroke mm(in.)	-----	180	(7.09)
Displacement Liter(in. ³)	-----	49.0	(2992)
Compression Ratio	-----	14.5 : 1	
Dry Weight - Engine only - kg(lb)	-----	5320	(11731)
Wet Weight - Engine only - kg(lb)	-----	5600	(12348)

PERFORMANCE DATA

Idling Speed -rpm	-----	600~650	
Maximum Overspeed Capacity - rpm	-----	1870	
Moment of Inertia of Rotating Components J- kg·m ² (lb·ft ²)	-----	20.22	(1920)

ENGINE MOUNTING

Maximum Bending Moment at Rear Face of Flywheel Housing - N·m(lb·ft)	-----	4413	(3256)
--	-------	------	--------

AIR INLET SYSTEM

Maximum Intake Air Restriction (Includes piping)- kPa (in.H ₂ O)	-----	3.92	(15.7)
Maximum Allowable Intake Air Temperature- °C (°F)	-----	45	(113)

EXHAUST SYSTEM

Maximum Allowable Back Pressure - kPa (in.H ₂ O)	-----	4.41	(17.7)
---	-------	------	--------

LUBRICATION SYSTEM

Oil Pressure at Idle - MPa (psi)	-----	0.2~0.3	(29~43)
at Rate Speed - MPa (psi)	-----	0.5~0.6	(71~86)
Maximum Oil Temperature- °C (°F)	-----	110	(230)
Oil Capacity of Marine Pan High - liter (U.S.gal)	-----	200	(52.8)
Low - liter (U.S.gal)	-----	158	(41.7)
Total System Capacity (Includes Oil Filter) - liter (U.S.gal)	-----	230	(60.8)
Maximum Installation Angle		Front Up	----- 12.5°
		Front Down	----- 15°
Maximum Instantaneous Operating Angle		Front Up	----- 30°
(Engine Level)		Front Down	----- 30°
		Side to Side	----- 22.5°

COOLING SYSTEM

Coolant Capacity of Jacket(Engine only) - liter (U.S.gal)	-----	111	(29.3)
Coolant Capacity of Air cooler(Engine only) - liter (U.S.gal)	-----	14	(3.7)
Maximum External Friction Head at Engine Outlet-MPa(psi)	-----	0.034	(5.0)
Recommended Static Head of Coolant above Crankshaft Center - m(ft)		MAX.	----- 10 (32.8)
		MIN.	----- 7 (23.0)
Standard Thermostat (Modulating)Range- °C (°F)	-----	71~85	(160~185)
Maximum Coolant Temperature at Engine Outlet- °C (°F)	-----	95	(203)
Recommended Coolant Temperature at Engine outlet- °C (°F)	-----	80	(176)
Minimum Coolant Expansion Space-% of System Capacity	-----	10	
Maximum Coolant Temperature at Inter Cooler Inlet, PTAW type- °C (°F)	-----	see page 4/4	

The specifications are subject to change without notice.

FUEL SYSTEM

Fuel Injection Pump	-----	Mitsubishi PS6 Type x 2
Maximum Suction Head of Feed Pump - kPa (in. Hg)	-----	14.7 (4.3)
Maximum Level of Fuel Tank - m	Continuous Use	----- 5.0
	Stand-by Use	----- 2.0
Minimum Fuel Oil Supply Pipe Inner Diameter - mm(in.)	-----	20 (0.79)
Minimum Fuel Oil Leak Pipe Inner Diameter - mm(in.)	-----	20 (0.79)

STARTING SYSTEM

Battery Charging Alternator - V-Ah	-----	24-35
Starting Motor Capacity - V -kW	-----	24-7.5×2
Maximum Allowable Resistance of Cranking Circuit - m Ω	-----	1.5
Recommended Minimum Battery Capacity		
At 5°C (41°F) and above - Ah	-----	300
Below 5°C (41°F) through -5°C (23°F)	-----	600
Cranking Ampere of Starter at 5°C (41°F) / -5°C (23°F)		
Static Ampere -A		380 × 2 / 480 × 2
Momentary Ampere -A		720 × 2 / 920 × 2

ACCESSORY EQUIPMENT

Air Cleaner	Silencer Type
Exhaust Manifold	Air Cooled
Turbocharger	Air Cooled
Air Cooler	Fresh Water Cooled
Breather	Conduction Type
Governor	Hydraulic PSG Type
Fuel Injection Pump	
Fuel Feed Pump	
Fuel Injection Pipe	Single walled Type
Fuel Injection Nozzle	
Fuel Filter	Paper Element Type
Lubricating Oil Pump	
Lubricating Oil Cooler	
Lubricating Oil Filter(Full-Flow)	Paper Element Type
Lubricating Oil Filter(By-Pass Flow)	Paper Element Type
Oil Pan	Large Capacity,steel
Cooling Water Pump (Jacket water)	
Cooling Water Thermostat(Jacket water)	
Starter	Earth Float Type
Alternator	Earth Float Type
Stop Solenoid	DC24V-15A
Engine Support	Marine Type
Accessory Drive	Front Drive Pulley

ACCESSORY EQUIPMENT(LOOSE SUPPLY)

Relay Safety	For Starter
Jack Bolt	
Companion Flange	
Standard Tools	
Standard Spare Parts	

The specifications are subject to change without notice.

ENGINE RATING

All data represent net performance according to ISO3046 with standard accessories such as fuel injection pump, water pump L.O. pump and charging alternator under the condition of 100kPa(750 mm Hg), barometric pressure 298K(25°C) ambient temperature and 30% relative humidity.

0

ITEM Engine Model	UNIT	Propulsion use			Generator use		
				-Y3MPTAW-3			
Test cycle (ISO 8178)				HD			
Engine Speed	min ⁻¹			E3			
No. of Cylinders				1600			
Bore	mm (in.)	12					
Stroke	mm (in.)	170 (6.69)					
Displacement	liter (in. ³)	180 (7.09)					
Brake Horse Power	kW (HP)			49.03 (2992)			
Brake Mean Effective Pressure	MPa (psi)			820 (1100)			
Mean Piston Speed	m/s (ft/min)			1.25 (181)			
Maximum Regenerative Power Absorption Capacity	kW (HP)			9.6 (1890)			
Intake Air Flow	m ³ /min (CFM)			128 (172)			
Exhaust Gas Flow	m ³ /min (CFM)			78 (2754)			
Coolant Flow	liter/min (U.S. GPM)			207 (7309)			
Coolant(Jacket water) Pressure (water pump outlet)	MPa (psi)			1720 (454)			
Coolant Flow to Inter Cooler (Max. Flow: 320L/min)	liter/min (U.S. GPM)			0.15 (22)			
Oil Flow	liter/min (U.S. GPM)			200 (53)			
Radiated Heat to Ambient	kJ/hr (BTU/min)			510 (135)			
Heat Rejection to Coolant	kJ/hr (BTU/min)			246576 (3896)			
Heat Rejection to Inter Cooler (PTAW Version)	kJ/hr (BTU/min)			1479458 (23375)			
Heat Rejection to Exhaust	kJ/hr (BTU/min)			1315074 (20778)			
Cooling system	Direct Sea Water Cooling Max. sea water temp. at inter cooler inlet			2224557 (35148)			
	Intermediate Fresh Water Cooling Max. fresh water temp. at inter cooler inlet			N/A			
	Radiator Cooling Max. coolant temp. at inter cooler inlet			Max. 32°C (When sea water temp. 25°C)			
Noise Level (1 m height & distance) (excludes, Intake, Exhaust)	dB(A)			-			
Maximum No Load Governed Speed	min ⁻¹			1720			

The specifications are subject to change without notice.

APPLICATION : MARINE



Pub. No. T0207-0016E 4/4