

STAMFORD®**HC4**

| Model | HC4 |
|-----------------------------------------|-----|
| Maximum continuous rating at 50Hz (kVA) | 400 |
| Maximum continuous rating at 60Hz (kVA) | 500 |

| Specifications | |
|--------------------------------|------------------------|
| Voltage Range | 380-690 |
| Poles | 4 |
| Technology | Wire Wound |
| AVR | Analogue |
| Voltage sensing | 2-Phase |
| Bearing Arrangement | Single |
| SAE Adaptors | 0, 1, 2 |
| Terminals | 12 |
| Material Insulation Class | H |
| Excitation System | Self exciting |
| Ingress Protection | IP23 |
| Connection with other machines | Paralleling capability |

| Optional Features | |
|--------------------------|------------------------------|
| Excitation System | PMG |
| Bearing Arrangement | Double |
| Ingress Protection | IP23 Air Filters |
| Output configurations | 1 phase re-connectable |
| Voltage sensing | 3-Phase sensing |
| AVR | Digital |
| Temperature monitoring | Winding RTDs |
| Temperature monitoring | Thermistors |
| Environmental protection | Anti-condensation Heaters |

| Designed For | |
|----------------------------|---|
| Grid Code Compatible | ● |
| Marine Auxiliary | ● |
| Oil & Gas Auxiliary | ● |
| Combined Heat & Power | ● |
| Critical Protection & UPS | ● |
| Continuous Power & Standby | ● |

| Prime Movers | |
|---------------|---|
| Diesel Engine | ● |
| Gas Engine | ● |

**DIMENSIONS**

Drawings represent standard design
All dimensions in millimetres (mm)

