

STAMFORD®

P0



| Model | P0 |
|---|----|
| Maximum continuous rating at 50Hz (kVA) | 20 |
| Maximum continuous rating at 60Hz (kVA) | 22 |

| Specifications | |
|--------------------------------|------------------------|
| Voltage Range | 380-600 |
| Poles | 2, 4 |
| Technology | Wire Wound |
| AVR | Analogue |
| Voltage sensing | 2-Phase |
| Bearing Arrangement | Single |
| SAE Adaptors | 2, 3, 4, 5 |
| Terminals | 12 |
| Material Insulation Class | H |
| Excitation System | Self exciting |
| Ingress Protection | IP23 |
| Connection with other machines | Paralleling capability |

| Optional Features | |
|--------------------------|---------------------------|
| Excitation System | EBS |
| Bearing Arrangement | Double |
| Output configurations | 1 phase re-connectable |
| Temperature monitoring | Thermistors |
| Environmental protection | Anti-condensation Heaters |

| Designed For | |
|----------------------------|---|
| Marine Auxiliary | ● |
| Oil & Gas Auxiliary | ● |
| Telecommunications | ● |
| Mobile Construction | ● |
| Combined Heat & Power | ● |
| Critical Protection & UPS | ● |
| Continuous Power & Standby | ● |

| Prime Movers | |
|---------------|---|
| Diesel Engine | ● |
| Gas Engine | |

DIMENSIONS

Drawings represent standard design
All dimensions in millimetres (mm)

